CHMUTINA, Ye.P.; KOLOYARTSEVA, T.I.

Physical development of kindergarten children in Khabarovsk in 1959. Vop. okh. mat. 1 det. 6 no.4:73-77 Ap '61. (MIRA 14:6)

1. Iz kafedry pediatrii (mav. - dotsent G.3.Postol) Khabarovskogo meditsinskogo instituta (dir. - prof. S.K.Nechepayev).

(KHABAROVSK\_\_CHILDREN\_\_GROWTH)

KOLOYARTSEVA, Ye. I.: "The general pedagogic activity of L. K. Shleger in the field of pre-school training." Min Education RSFSR. Moscow State Pedagogical Inst imeni V. I. Stalin. Moscow, 1956. (Dissertation for the Degree of Candidate in Pedagogical Sciences).

Source: Knizhnaya letopis' No. 28 1956 Moscow

ACC NR: AP6015707.

SOURCE CODE: UR/0413/66/000/009/0109/0109

INVENTOR: Koloydenko, A. L.

ORG: None

TITLE: A pneumatic intermittent delay unit. Class 42, No. 181401 [announced by the Voronezh Affiliate of the experimental Design Office of Automation (Voronezhskiy filial opytno-konstruktorskogo byuro avtomatiki)]


SOURCE: Izobreteniya, promyshlennyye obraztsy, tovarnyye znaki, no. 9, 1966, 109

TOPIC TAGS: pneumatic computer, delay mechanism

ABSTRACT: This Author's Certificate introduces a pneumatic intermittent delay unit which contains vessels with limp diaphragms, diodes, pulsating resistors, a cycle delay and contacts. Accuracy is improved by connecting the working chambers of the vessels with limp diaphragms in series with each other through diodes. The working chamber of the first vessel is connected through a pulsating resistor to the input line, while the working chamber of the last vessel is connected through a pulsating resistor and the cycle delay to the output line. The control chambers of the vessels with limp diaphragms are interconnected through a single line, and connected by contacts to sources of supply pressure and metering level pressure. The control chambers of the pulsating resistors, the cycle delays and the contacts are connected to a discrete signal source.

Cord 1/2

UDC: 681.142-525



ACC NR: AT6021728

SOURCE CODE: UR/0000/66/000/000/0057/0070

AUTHOR: Gorelik, N. G.; Koloydenko, A. L.; Podol'skiy, T. S.; Sokolov, V. N.; Stukalov, A. M.; Fudim, Ye. V.

ORG: none

TITLE: Design of pneumatic computing and control systems and their application in the automation of synthetic rubber production

SOURCE: AN SSSR. Institut avtomatiki i telemekhaniki. Pnevmoavtomatika (Pneumatic automation). Moscow, Izd-vo Nauka, 1966, 57-70


TOPIC TAGS: pneumatic control, pneumatic device, automatic pneumatic control, synthetic rubber, rubber working machinery, industrial automation, automatic control equipment


ABSTRACT: Pneumatic control systems used for automated production of synthetic rubber are described. Table I summarizes the types, functions, and typical applications of pneumatic devices in manufacturing of rubber. Three examples of specific applications follow. Process optimization of contact breakdown of alcohol into divinyl. This process depends on the catalyst activity, the composition of the contact mixture, feed of alcohol vapor, and catalyst temperature. The first two parameters are considered to be random disturbances and the last two, the controlling forces. The quality indicator of the process is the divinyl output for alcohol input. A block diagram of the system is

Card 1/4


ACC NR: AT6021728	TABLE 1	
ype of device	Function	Typical applications
	Processing of primary data	Noise filtering Time delay Linearization
		Decoding of chromatographic data
Computing	Computation of complex parameters and generation of appropriate signals to control system	Final product output computation  Computation of economic indicators  Averaging
		Change of the control system from multi-loop to single loop when a predetermined criterion is reached
Control	Control according to a time program of the pro- cess parameters	Automatic ratio correction of two fractions fed when a predetermined criterion is reached
Card 2/4		

		TABLE 1 (Continue	d)
			The selection of a maximum (minimum) signal from a set of n signals Gate valve switching in flow lines Control through optimizing systems
		Control in response to quality indicators	Stabilization Optimization
er 2 wher alues of perform he diviny indicat icator si ates stabeed. The	e the liquid and divinyl content these functions l concentration ors according to gnal with respetilization systemes design and per	ad gaseous product component and the condensate density of the condensate density of the condensate density of the condensate density of the condensate of t	is 1 is fed into isothermic conden- its are separated to determine the cy. Densitometer 4 and chromatograph output of the chromatograph to make stem 6 computes the values of quali- Device 7 averages the quality in- its noise. Limit controller 8 regu- control the temperature and alcohol culator and the controller are given arcmatograph is intended for automa-





differences of incoming signals, the normally closed contact (ncc) of the pulsating resistor is connected to one incoming channel, and the normally open contact (nvc) is connected to the working chambers of two pulsating capacitors and by the ncc to the output amplifier. The upper capacitor is connected by the nvc to a second input channel and by the ncc to the power supply channel; the lower capacitor is connected by the nvc to the nower supply channel and by the ncc to the exhaust. Orig. art. has: 1 figure.  SUB CODE: 13, 09/ SUBM DATE: 15May64/ ATD PRESS: 5104	L 07454-67 ACC NR: AP6035742				
has: 1 figure.  SUB CODE: 13, 09/ SUBM DATE: 15May64/ ATD PRESS: 5104	resistor is connected is connected to the worthe output amplifier.	to one incoming chan- rking chambers of two The upper capacitor to the power supply	nel, and the norm o pulsating capac is connected by channel; the low	ally open con itors and by the nvc to a er capacitor	the ncc to second input is connected
	has: 1 figure.				
Card 2/2 (3)m	SUB CODE: 13, 09/ SUBM	DATE: 15May64/ ATD	PRESS: 5104		
Card 2/2 1)m					
Card 2/2 10m					
Cord 2/2 / ) m	•				
Card 2/2 10m					
Card 2/2 /3mg					
	Card 2/2 /3m	•			



	ACC NR: AP6011261	0
	tacts. In order to maintain a direct ratio between the discharge and absolut sure, or a positive pressure differential, the containers have common wall a airtight limp membrane. Orig. art. has: I figure.	ite pres- iade of an [SA]
	SUB CODE: 14, 10/ SUBM DATE: 17Sep63/ AAD PRESS:4228	
	200 CODE: 144 TOLE SOUTH DATA SELECTION OF S	
	karanca arang mengendigi ng diagrifika sebiggi kalikana itang misi inak diagrifikan diagrifikan sebigai kalika	
**		
	jaus suginus arratopusabas – utsiar pri krapiąlijkytosi lygi justyšši žiarar priostura critar sumos imajovertjū	KARATA TE
	▲	
- 1	🖟 a promotion of the complete and the complete of the complet	جاري بيرويطي ك
	Patrick and a distributed from the grafter warp blooms of the state of the control of the state of a state for	
	The state of the s	1 min
	√ nikon nisi filolo säiteliik gludigi eikonisifikininitsi täättiki valkaj takkit, vatkon nii liin johan keushankit	
-14	وكوالكرابين الكراب والمنافر المعافرات والمتقافل والمهافية القيارات والكوار المهاب والكرابي والمعاور والمرابية	ર હતું, ", હે લોકુકું છે
	Card 2/2 3K	
	Card 2/2 (a)	

KOLOYE, V.

POLAND/Nuclear Physics - Penetration of Charged and Neutral

Particles Through Matter.

Abs Jour : Ref Zhur - Fizika, No 4, 1957, 8856

Author : Koloye, V.,

Inst : Physics Institute, Polish Academy of Sciences.
Title : Effective Cross Section of a Molecule of Methyl

Mercaptane for the Scattering of Slow Neutrons.

Orig Pub : Vyul. Pol'skoy AN, 1956, Otd. 3,4, No 5, 263-265

Abstract : The cross section for the scattering of slow neutrons by

a molecule of methyl mercaptane. The method developed in previous works by the author (Referat Thur Fizika, 1956, 9868) is used. The effect of the vibrations of the molecule are taken into account under the assumption that it is the same as for methane. Ideas concerning the role

of association are stated.

Card 1/1

KCLCYEV, B. A.

Casetes

Landowning and land tenure of the Mozdok Cssetes Sov. etn. no. 1, 1952.

9. Monthly List of Russian Accessions, Library of Congress, August 1957, Uncl.

5/196/61/000/009/027/052 E194/E155

Balagurov, V.A., and Kolozeznyy, E.A. AUTHORS:

Calculation of the external characteristics of TITLE:

synchronous generators with permanent magnetic field

PERIODICAL: Referativnyy zhurnal, Elektrotekhnika i energetika, no.9, 1961, 22, abstract 9I 152. (Vestn. elektroprom-sti no.2, 1961, 41-44)

The calculation is made using a working diagram of the magnet and a vector diagram of voltage. Allowance is made for reduction in the magnetic flux of the magnet with increasing generator load and for field realignment resulting from armature reaction and voltage drop in the ohmic resistance and reactance. The working diagram of a magnet for a generator with starconnected rotor without pole pieces is used to establish a relationship between the longitudinal m.m.f. of armature reaction and the longitudinal e.m.f. in the armature winding used to construct the external characteristics. Voltage vector diagrams of synchronous generators with permanent magnetic field are the same in principle as those of generators with electro-magnetic Card 1/2


Calculation of the external ...

S/196/61/000/009/027/052 E194/E155

excitation. The article considers the construction of the external characteristics of generators with star-connected rotors without pele pieces and of generators with beak-shaped rotors and commutator type.
6 illustrations, 6 literature references.

Abstractor's note: Complete translation.]

Card 2/2




KOLOTHUK, V.J. ENG. (Reviewer)

POTOTAROVA, B.A.

"Design construction and installation of a braking device preventing the reverse motion of the disc in electric meters." Eng. Ya. P. Kalita, B.A. Penomarova, Reviewed by Eng. V.I. Kolozhuk. Prom. energ. 9, no.8, August 1952.

Monthly List of Russian Accessions, Library of Congress, November 1952, UNCLASSIFIED



IGONON, P.G., inzh.; SVITKIN, V.V., inzh.; MITROFANOV, M.G., kand.tekhn.nauk; SLEPTSOV, Yu.S., inzh.; KOLOZHVARI, A.A., inzh.; PASHENKO, M.A., inzh.; ZHIVOLUPOVM.A., inzh.; Prinimali uchastiye: MUSHENKO, D.V.; TSYSKOVSKIY, V.K.; SHCHEGLOVA, TS.N.; FREYDIN, B.G.; FYL'NIKOV, V.I.; LEVINA, M.I.; LEVIN, A.I.; LUR'YE, Ye.I.; BAYKINA, T.A.; UDOVENKO, S.A; MARCHENKO, T.A.

Effect of the method of liquid paraffin oxidizing on the yield and quality of the obtained fatty acids. Masl.-zhir.prom. 28 no.11:20-23 N '62. (MIRA 15:12)

1. Groznenskiy nauchno-issledovatel'skiy neftyanoy institut (for Igonin, Svitkin, Mirtofanov, Sleptsov, Kolozhvari, Pashenko, Zhivolupov).

2. Vsesoyuznyy nauchno-issledovatel'skiy institut neftekhimicheskikh protsessov (for Mushenko, TSyskovskiy, Shcheglova, Freydin, Pyl'nikov, Levina, Levin).

3. Lengiprogaz (for Lur'ye, Baykina).

4. VNIISINZh (for Udovenko, Marchenko).

(Paraffins) (Acids, Fatty)

IGONIN, P.G.; SVITKIN, V.V.; SLEPTSOV, Yu.S.; KOLOZHVARI, A.A.; PASHENKO, M.A.; GLOTSER, Ye.M.

Oxidation of naphthenic hydrocarbons. Nefteper. i neftekhim. no.1:17-19 '63. (MIRA 16:10)

1. Groznenskiy nauchno-issledovatel'skiy institut.

L\_10227-63 EMP(j)/EPF(c)/EWT(m)/BDS-AFFTC/ASD/APGC-Pc-L/Pr-L-EM/EM/MAY/DJ ACCESSION NR: AP3000503 S/0065/63/000/005/0034/0038

AUTHOR: Igonin, P. G.; Svitkin, V. V.; Kolozhvari, A. A.; Sleptsov, Yu. S.;

TITIE: Oxidation of isoparaffinic hydrocarbons

SOURCE: Khimiya i tekhnologiya topliv i masel, no. 5, 1963, 34-38

TOPIC TAGS: oxidation, isoparaffinic hydrocarbons, isoparaffinic acids, plasticizers, flotation agents, synthetic lubricant esters, motor alkylate

ABSTRACT: Isoparaffinic anids see of interest as starting materials for the production of plasticizers. If lotation agents, and synthetic lubricant esters. The synthetic fatty acid pilot plant of GrozNII was used for oxidation of motor alkylate containing no nytrocarbons complexing with urea. The oxidation was done with air at 1200 and a manganese-potassium soap catalyst to an acid number of 70 mg ROH per gram. The oxidate was saponified and the acids isolated and fractionated. Nearly 90% forms no complex with urea. When compared to fractions of synthetic fatty acids distilling within the same limits, the acids obtained in this work have higher acid numbers and lower pourpoints. Heat treatment strongly reduces the


Card I/2

 content of petroleum ether instables.	solubles formed in	the oxidation. O	rig. art. has: 6
ASSOCIATION: GrozNIT SUBMITTED: 00	DATE ACQUE 12	Jun63	ENCL: 00
SUB CODE: CH	NO REF SOV: 0		OTHER: COL
			6
() () () () () () () () () () () () () (			

IGONIN, P.G.; SVITKIN, V.V.; SLEPTSOV, Yu.S.; KOLOZHVARI, A.A.;
PASHENKO, M.A.; GLOTSER, Ye.M.

Oxidation of naphthenic hydrocarbons. Trudy GrozNII no. 15:
298-302 '63.

(MIRA 17:5)



ACCESSION NR: AT4016004

8/2625/63/000/015/0323/0332

AUTHOR: Igonin, P.G.; Switkin, V.V.; Kolozhvari, A.A.; Sleptaov, Yu. S.;

TITLE: Oxidation of isoperaffinic hydrocerbons

SOURCE: Grozny\*y. Neftyanoy nauchno-issledovatel'skiy institut. Trudy\*, no. 15, 1963. Tekhnologiya pererabotki nefti i gaza. Neftekhimiya (Technology of processing petroleum and gas. Petroleum chemistry), 323-332

TOPIC TAGS: hydrocarbon, hydrocarbon oxidation, organic acid, alkylate, motor alkylate, isoparaffinic hydrocarbon

ABSTRACT: Since the paraffins which are oxidized in the production of synthetic fatty acids also contain isoparaffinic hydrocarbons, the authors studied the oxidation of a motor alkylate consisting entirely of hydrocarbons which do not form complexes with carbamide. Both the entire motor alkylate and the 200-300C fraction were first oxidized under laboratory conditions on a glass column at 117 or 125C, and then on the SZhK experimental apparatus at 120C with mand K soaps as catalysts. The density, molecular weight, acid number,

ACCESSION NR: AT4016004

ether number, iodine number and other characteristics of the products are tabulated for each case. The results show that motor aklylates must be oxidized under a pressure of 2-3 atm. The theoretical scheme for the preparation of acids having an iso structure is analogous to that used for the preparation of synthetic fatty acids. However, the acids obtained from motor alkylates consist almost entirely of acids which do not form complexes with carbamide. During the oxidation of isoparaffinic hydrocarbons, a large number of products which are insoluble in petroleum ether are formed, the acid content of which sharply decreases after thermal treatment. The oxidation of motor alkylates yields acids, the fractions of which are similar to the fractions of fatty acids, but which have lower solidification points and acid numbers. Orig. art. has: 8

ASSOCIATION: Neftyanoy nauchno-issledovatel'skiy institut, Grozny\*y (Petroleum Scientific Research Institute)

SUBMITTED: 00

. .

DATE: MO: 3Llands

EMCL: 00


SUB CODE: OC


NO BEY SOVE OUR


OTHER: 000


Card 2/2


OTHER! GOO














KOLOZSVARI, Gabor, okleveles foldmaromernok, egyetemi adjunktus

Preliminary accuracy testing of break-through measurements. Bany lap 97 no.3:164-169 Mr '64.

1. Chair of Geodesy and Mine Surveying, Technical University of Heavy Industry, Miskolo.


KOLOZSVARI, Gabor, okleveles foldmernomernok, egyetemi adjunktus

Some remarks about the use of invar steel bands. Bany lap 96
no.62393-394 Je \*\*63.

L. Nebezipari Muszaki Egyetem Geodemiai es Banyamerestani
Tanszek, Miskolo.

Development of the interepithelial junction region in the closes of domestic hens. Trudy Tbil. GU 88:99-106 '63.  (MIRA 18:8)
l. Kafedra gistologii Tbilisskogo universiteta.


# Application of special motor vehicles in the construction industry. Epites smelle 6 no.5:160-163 \*62. 1. Epitesugyi Miniszterium Szallitasi Igazgatosaganak fomernoke.





SZABO, Istvan, dr.; GERTHEISZ, Antal; KOLOZSVARY, Szbolczne; RIEDL, Gyula

Hungary's forestry librarianship. Erdo 11 no.9:415-419 S !62.

Konyvtaros, Erdomernoki Foiskola, Sopron (for Szabo).
 Tudomanyos munkatars, Orszagos Mezogazdasagi Konyvtar (for Gertheisz).







1,	KULP, K.
2.	tissin (600)

 Labor Productivity
 Intefactory schools for generalization and exchange of progressive practice. Prof. soiuzy 8, no. 3, 1953

Monthly List of Russian Accessions, Library of Congress,


APPROVED FOR RELEASE: 06/13/2000 CIA-RDP86-00513R000824010003-3"

1953. Unclassified.

BARABANOVA, V.N.; KOZHENYAKIWA, L.K.; KOLFACHENKO, M.A.


Hew flowshest for refining crude molybdenum concentrates at the Tyrny-Aus Ore-Dressing Plant. TSvet.mst. 33 no.1:23-25 Ja '60.


1. Tyrny-Ausskiy kombinat.
(Molybdenum-Metallurgy) (Tyrny-Aus-Ore dressing)



The role of establishing two types of geographic data. Vop. psikhol. 3 no.	(MIRA 10:9)	
1. Institut psikhologii Akademii pedagogicheskikh nauk RSFSR,		
Koskva. (Geography-Study and teaching)		
•		
· .		
	4	
	•	

			0.00
		-	1
			• >
		1B 1028F 765 7000 7012 70070 70070	
1 6	VAR CAPSO19039	DZW. SOO T OZA 6442. 24 SOOS OF	NOSEL CONTRACTOR
4	Travin, K. P.; Kolpachev, Yu. G.; Okhotr F; Grishin, M. S.; Sandakov, Ya. A.;	Trevev, V. G.; Firevev, V. G.; Plushevskiy,	
PERSONAL PROPERTY OF A STATE OF THE PERSONAL PROPERTY OF THE PERSONAL P			- 44 - 44 - 44 - 44 - 44 - 44 - 44 - 4
	mank for storage and transportation of	liquids. Clase 37, No. 172022	
		v, no. 11, 195, 7)	
	liquid storage, tank		
	This Author's Certificate introduces:  i a liquid. The unit is made of an ela	1. A tank for storage and trans	; <del>-</del> ,
1 **	the with a neck and a ring. The float:	ing ring is mounted on the outal	.de
	and can be replaced so that buckling	of the rim of the neck can be	
avoided	in case the ring is damaged. 2. A modifi-	cation of this tank in which the	
	ring is made replaceable by covering it	with a sleeve which is rastened	το '
	straps.		1
	11 Mr. none		
	and the second s		
			was said a
District of the second			





s/109/60/005/05/021/021 E140/E435

AUTHORS:

Bur'yanov, P.D., Buts, V.P., Kolpachev, Yu.I., Zheleznov, L.F. and Kupchinov, N.F.

TITLE:

Letter to the Editor: On the Publication of the Article "Ribbon Electron Beams Vin a Longitudinal Homogeneous Magnetic Field with Arbitrary Degree of Cathode Screening"

Cathode Screening"

PERIODICAL: Radiotekhnika i elektronika, 1960, Vol 5, Nr 5, p 880 (USSR)

A brief letter indicates that Alyamovskiy's results (Ref 1) have been previously obtained by Porev at the ABSTRACT:

Taganrog Radio Engineering Institute (Ref 2, 3, 4).
There are 4 Soviet references.

Card 1/1

CIA-RDP86-00513R000824010003-3" APPROVED FOR RELEASE: 06/13/2000

# KOLPACHEVA, MIP.

USSR/Chemical Technology. Chemical Products and Their

I-9

Application - Silicates. Glass. Ceranics. Binders.

Abs Jour : Referat Zhur - Khimiya, No 4, 1957, 12513

Author

: Kolpacheva M.P.

Inst

: Voronezh University

Title

Effect of Potash and Sulfuric Acid on Sedimentation of

Western Kazakhstan Sands by Clay

Orig Pub

: Tr. Voronezhsk. un-ta, 1955, 35, 75-83


Abstract


Investigated was the effect of added  $K_2CO_3$  (0.01 N) and  $H_2SO_4$  (0.005 N) on sedimentation of sand by clay depending on the turbidity of the slurry, fractional composition of the clay, duration of slurry feed and water pressure gradients. In the sedimentation of sands of three areas by clay secured from the same areas, the beneficial effect of the above-stated additives has been ascertained and moditions are stated to attain their


optimal effects.


Card 1/1

- 65 -









BABIN, Yo.P.; KOLPAKCHI, A.A.

Disproportionation and conjugated alkylation of alkylchlorobenzenes in the presence of AlCl<sub>3</sub>, AlCl<sub>2</sub>.H<sub>2</sub>PO<sub>4</sub>, and AlCl<sub>3</sub>.CH<sub>3</sub>NO<sub>2</sub>. Zhur. prikl. khim. 38 no.7:1640-1643 Jl. 65. (MIRA 18:7)

KHISAMUTDINOV, A.G.; MUKHUTDINOVA, R.G.; KOLPACHIKHIN, F.B.

Evaluation of antidiphtheria immunity by means of a spintest. Vop. okh. mat. i det. 5 no. 2:41-44 Mr-Ap 160. (MIRA 13:10)

l. Iz Kazanskogo nauchno-issledovatel'skogo instituta epidemiologii i gigiyeny.


(DIPHTHERIA-PREVENTIVE INOCULATION)

ALATYRTSEVA, I.Ye., KOLPACHIKHIN, F.B.; AMFITEATROVA, N.F.; SHAROVSKAYA, V.N.; DVORKINA, A.I.; MEL'NIKOVA, V.K.; BERZON, I.G.

Intranasal revaccination against diphtheria. Report No. 1. Vop.okh. mat.i det. 7 no.4:29-32 Ap '62. (MIRA 15:11)

1. Iz Kazanskogo nauchno-issledovatel skogo instituta epidemiologii, mikrobiologii i gigiyeny.

(DIPHTHERIA—PREVENTIVE INOCULATION)



SOV/175-58-6-15/41

AUTHOR:

Kolpak P., Lieutenant Colonel

TITLE:

Friendship With the Unit's Veterans

PERIODICAL:

Tankist, 1958, Nr 6, p 22 (USSR)

ABSTRACT:

The author mentions the praiseworthy initiative taken by the secretaries of the various komsomol organizations. Master Sergeant Timonin, Sergeant Shatunov, First Lieutenant Ivonin, and Private first class Shapovalov have written to the unit's veterans. The replies received were from Master Sergeant F.F. Lenshin, bearer of the "Slava" ("Glory") orders, Reserve First Lieutenants barkovenko and Potapov and from the Hero of Soviet Union Major N.I. Kukhorenko.

Card 1/1

KOLPAK, P.V., inzh.; HELAN, G.S., inzh.

Resistance to faulting of ore-bearing and enclosing rocks in the
Stebnik potash deposit. Nauch. zap. Ukrniiproekta no.10:58-70 '63.

(MIRA 17:6)

KOLPAKCHI, A.A.; BABIN, Ye.P.

Effect of solvent on the kinetics of the alkylation of chlorobenzene with propylene. Zhur. fiz. khim. 37 no.11:2560-2563 N.63.

(MIRA 17:2)

1. Donetskoye otdeleniye instituta organicheskoy khimii.

Alkylation of chlorobenzene with isopropyl chloride in the presence of aluminum chloride. Kin.i kat. 3 no.6:855-860 N-D '62. (MIRA 15:12)

1. Institut organicheskoy khimii AN UkrSSR, Donetskoye otdeleniye. (Bemzene) (Propane) (Alkylation)

### BABIN, Ye.P.; KOLPAKCHI, A.A.

Relation of the rates of formation of isopropylbenzenes and equations for the composition of alkylation products of chlorobenzene with propylene in the pressence of aluminum chloride. Zhur. fiz. khim. 37 no.6:1371-1374 Je 163.

(MIRA 16:7)

1. Donetskoye otdeleniye instituta organicheskoy khimii.
(Benzene) (Alkylation)
(Chemical reaction, Rate of)

AUTHOR: Kolpakchi, L.M.

68-58-3-8/22

TITLE:

On the Problem of Decreasing the Volume of Control of Production (K voprosu sokrashcheniya ob'yema kontrolya

prolzvodstva)

PERIODICAL: Koka i Khimiya, 1958, Nr 3, pp 32 - 33 (USSR).

ABSTRACT: In view of a considerable improvement in the stability of the quality of products, a decrease in the volume of control analysis and tests is advocated. It is pointed out that the control personnel should be relieved from some of the duties and more responsibility taken by the operating personnel. A mechanical sample divider used on the works is outlined (figure). The necessity of improvement in the mechanisation of preparation of samples is stressed. There is I figure.

ASSOCIATION: Zaporozhskiy koksokhimicheskiy zaved (Zaporozh'ye Coke Oven Works)

Card 1/1

AUTHOR:

Kolpakchi, L. M.

68-58-6-15/21

TITLE:

Securing a Uniform Moisture Content of Coke (Obespecheniye ravnomernoy vlazhnosti koksa)

PERIODICAL: Koks i Khimiya, 1958, Nr 6, pp 55-56 (USSR)

ABSTRACT: In order to determine optimum conditions securing the stability of the moisture content of coke, the influence of the following factors was investigated: size distribution of coke, uniformity of its discharging into the quenching wagon, uniformity of quenching with water in the quenching tower, the quality of water used for quenching, the time during which coke is retained on the wherfe, method of sampling and sample preparation. It is concluded that in order to obtain coke of a uniform moisture content the following conditions should be maintained: 1) a uniform distribution of coke in the quenching wagon; 2) standard quenching conditions in the quenching tower; 3) a constant quality of quenching water and 4) an automatic operation of coke wharfe. It is also considered that the weight of coke sample taken for the

Card 1/2 of coke oven and that the sample division should be done

after crushing to -13 mm and not before as is done at present.

There are 2 tables.

ASSOCIATION: Zaporozhskiy koksokhimicheskiy zavod (Zaporozh'ye Coal-tar Chemical Plant)

- 1. Coke--Moisture content 2. Humidity--Control systems
- 3. Water--Applications

Card 2/2

KOLPAKOV, A.

36046 Mekhanizirovannyy maslozavod iz sbornykh konstruktsiy. Moloch prom-st', 1949, No. 11, s. 12-17


SO: Letopis' Zhurnal'nykh Statey, Vol. 45, 1949

ANTIPIN, L., inzh.; KOLPAKOV, A., inzh.

Polymers grown by aluminum. IUn. Tekh. 4 no.5122-26
My 'GO.

(MEA 13:7)

(Polyethyloza) (Aluminum organic compounds)



# KOLPAKOV. A.A.

Changes in the excitability of the cervical sympathetic nerve in cats during shock associated with block transfusion. Vrachidelo no.9:987 S 157. (MIRA 10:9)

1. Kafedra patelegicheskoy fiziologii (zav. - prof. C.A.Begemelets)
Kiyevakogo instituta usovershenatvovaniya vrachey
(SHOCK) (BLCOD-TRANSFUSION)
(MERVORS SYSTEM, SYMPATHETIC)

KCLPAKOV, A.A., Cand Med Sci-- (diss) "Changes in the excitability of the new collection apparatus under rious influences and the course of the hemotransfusion shock with this background." Kiov, 1958. 14 pp (Kiev Order of Labor Red Banner State Med Inst in Acad A.A Bogomoletc) 200 copies (EL, 43-58, 118)

#### KOLPAKOV, A.A.

Changes in the excitability of carotid chemo-and pressoreceptors and the sympathetic nervous system of dogs following the transfusion of small doses of heterogenous blood. Nov.khir.arkh. no.2:62-65 Kr-Ap 158 (MIRA 11:6)

l. Kafedra patologicheskoy fiziologii (zav. - prof. O.A. Bogomolets) Kiyevskogo instituta usovershenstvovaniya vrache. Chernovtsy. Mediteinskiy institut, kafedra patofiziologii. (BLOOD.--TRANSFUSION)

(CAROTID SINUS-INNERVATION) (NERVOUS SYSTEM SYMPATHETIC)

#### CKOLPAKOV, A.A.

Changes in reflexes from chemo- and baroreceptors of the sinocarotid zone caused by a general action of novocaine. Fiziol. shur. [Ukr.] 4 no.6:841-843 N-D '58. (MIRA 12:3)

1. Kiyevskiy meditsinskiy institut.
(HOVOCAINE) (CAROTID SINUS)
(BLOOD-TRANSFUSION)

# Influence of mustard plasters on the excitability of the vegetative

portion of the nervous system and on the reflexes from the carotid baroreceptors. Vrach.delo no.7:757 J1 '59. (MIRA 12:12)

1. Kafedra patofiziologii (zav. - prof. D.S. Chetvertak) Chernovitskogo meditsinskogo instituta. (MUSTARD--PHYSIOLOGICAL EFFECT) (NERVOUS SYSTEM, AUTONOMIC) (CAROTID SINUS--INNERVATION)

"Hypothermia" by B.A. Saakov. Reviewed by A.A.Kolpakov, M.L. Tarakhove kyi. Fiziol.zhur. [Ukr.] 6 no.2:274-275 Kr-Ap '60. (MIRA 13:7)					
1. Chornovetskiy mediteinskiy institut, kafedra patofisiologii					
i farmakologii. (HYFOTHERWIA)	(SAAKOV, B.A.)				
		•			
	,				

CHETVERTAK, D.S., prof.; KOLPAKOV, A.A. (Chernovtsy)

"Pathological physiology" by A.N. Hordiienko. Reviewed by D.S. Chetvertak, A.A.Kolpakov. Vrach. delo no. 1:136-137 '61.


(MIRA 14:4)

(PHYSIOLOGY, PATHOLOGICAL) (HORDIIENKO, A.N.)

### KOLPAKOV, A.A.

Changes in the reflexes from the carotid chemoreceptors following chemical irritation of the skin. Vrach. delo no.4:142-143 Ap '61. (MIRA 14:6)

1. Kafedra patologicheskoy fiziologii (zav. - prof. D.S.Chetvertak)
Chernovitskogo meditsinskogo instituta.
(REFLEXES) (SKIN)



# KOLPAKOV, A.A., kand.med.nauk

\*Contraction and the contraction of the contraction

Effect of irritation of the cutaneous receptors by ustard plasters on the adrenegic and cholinergic properties of the blood. Vrach. delo no.8:119-120 Ag 163. (MURA 16:9)

l. Kafedra patologicheskoy fiziologii (zav. - dotsent L.N. Ochelenko) Chernovitskogo meditsinskogo instituta.

(MISTARD-THERAPEUTIC USE)

(BLOOD - ANALYSIS AND CHEMISTRY)

35597

S/133/62/000/004/003/008 A054/A127

1.1500

Kononov, B.Z.; Kolpakov, A.I.; Shurygin, G.D.; Engineers

TITLE:

AUTHORS:

Semicontinuous casting of stainless steel under synthetic slag

PERIODICAL:

Stal', no. 4, 1962, 313 - 315

TEXT: In casting titanium-containing stainless steel, a floating skin forms on the meniscus of the metal in the crystallizer, whose creases may cause severe flaws in the ingot. This skin contains a great amount of non-metallic inclusions. By casting in a shielding atmosphere (argon or propane) it is only possible to avoid those inclusions which are formed on the metal surface, whereas inclusions emerging from the depth of the bath cannot be trapped by this method. It was found more expedient to cover the metal meniscus with liquid slag which absorbs the non-metallic inclusions more thoroughly. The following synthetic slag compositions were tested [ (1) traces; (2) heat; ]:

Плавка СаF, SiO, CaO Na<sub>1</sub>O MnO FeO Fe<sub>2</sub>O<sub>5</sub> Cr<sub>2</sub>O<sub>6</sub> Al<sub>1</sub>O<sub>6</sub> TiO<sub>6</sub> MgO P<sub>6</sub>O<sub>6</sub> 8

A (2) 39.08 34.58 20.28 4.78 0.20 0.08 0.09 0.03 0.82 0.27 0.36 0.027 0.035

B E 41.52 34.48 14.79 4.98 0.25 0.05 0.09 0.09 0.02 0.23 0.23 0.26 0.032 0.072

B E 47.28 31.60 11.13 5.45 0.10 0.08 0.04 0.09 0.09 0.01 0.10 0.032 0.042

D F 40.20 34.24 20.28 4.62 0.18 0.08 0.04 0.070 0.33 Cacata 0.032 0.032 0.032

Card 1/3

S/133/62/000/004/003/008 A054/A127

Semicontinuous casting....

An ingot surface of good quality could be obtained only with a fluid slag, when over the entire perimeter of the slag meniscus a thin slag lining formed on the crystallizer walls. When the density of the slag increased and slag lumps formed which fell in the gap between the crystallizer wall and the ingot, a rough ingot surface was obtained. Consequently, the synthetic slag used should not contain much aluminum oxide which affects the viscosity of the slag, but more sodium oxide which ensures its required fluidity. The optimum slag quantity when casting 175 x 600 mm ingots of 4 - 6 tons, was about 60 - 75 kg, i.e. about 11 kg/1 ton steel. The slag is fed into the crystallizer in two batches: the first, when the crystallizer is filled with metal up to 100 mm and the second when half the ingot is cast. The yield of flawless product increased by 13 - 75% when synthetic stag was used during semicontinuous casting:

Metal waste in cropping Metal waste in roughing Slab rejects	A(with slag) 8,65 11,42 2.95	B(without slag) 6,9 10,2 13,8
Technological waste	18,11	18,35
Rejects of hot-rolled sheets	0,5	7,0

Card 2/3

# APPROVED FOR RELEASE: 06/13/2000 CIA-RDP86-00513R000824010003-3"

Semicontinuous casting....

S/133/62/000/004/003/008 A054/A127

corrosion	A(with slag)	B(without slag)
Yield of flawless hot-rolled	***	. 0,9
51.66.63	56,6	10.00
By improving the technology		42,85

By improving the technology of the process it is expected to raise the output beyond the present 59 - 71% level. There is hardly any difference in mechanical properties between the ingots of the conventional method and those produced by semi-continuous casting under synthetic slag. There are 4 figures and 4 Soviet-

ASSOCIATION: Krasnyy Oktyabr' Plant

KONONOV, B.Z., insh.; KOLPAKOV, A.I., insh.; SHURWEIN, G.D., insh.

Semicontinuous pouring of stainless stell under synthetic slag.
Stal' 22 no.4:313-315 Ap '62. (MIRA 15:5)

1. Metallurgicheskiy zaovd "Krasnyy Oktyabri".
(Continuous casting) (Steel, Stainless)

PITAK, N.V.; KONONOV, B.Z.; KOLPAKOV, A.I.; D'YACHENKO, A.I.

Service of refractories in a semicontinuous steel casting plant. Ogneupory 27 no.7:314-323 '62. (MIRA 15:8)

1. Ukrainskiy nauchno-issledovatel'skiy institut ogneuporov (for Pitak). 2. Volgogradskiy metallurgicheskiy savod "Krasnyy Oktyahr'" (for Kononov, Kolpakov, D'yachenko).

(Refractory materials) (Continuous casting)

KOLPAKOV, Aleksandr Lavrent'yevich; LOSEV, Vladimir Borisovich;
IVANOV, S.M., red.; ATROSHCHENKO, L.Ye., tekhn. red.

[Bountiful chemistry of organosilicon compounds] Shehedraia kremnitorganika. Moskva, Izd-vo "Znanie," 1962. 37 p. (Novoe v zhizni, nauke, tekhnike. IV Seriia: Tekhnika, no.21)

(Silicon organic compounds)

(MIRA 15:11)

KOLPAKOV, Aleksandr Lavrent'yevich, inzh.-khim.; CHERNIKOVA,
V.K., red.

[Metals in organic molecules] Metally v organicheskikh
molekulakh. Moskva, Izd-vo "Znanie," 1964. 38 p. (Novoe v zhizni, nauke, tekhnike. XI Seriia: Khimiia, no.4)
(MIRA 17:6)

BARCHENKO, N.I.; KOLPAKOV, A.M.; FIGURINA, Z.C.; TASHIN, V.I.,

Starshiy instruktor

Effect of balloon treevers on the breakage of staple yarn No.40 in unwinding. Tekst.prom. 21 no.6:35-36 Je '61.

(MIRA 15:2)

1. Glavnyy inzh. Istom'inskoy pryadil'no-tkatskoy fabriki (for Barchenko). 2. Nachal'nik ktatskogo proizvodstva Istomkinskoy pryadil'no-tkatskoy fabriki (for Kolpakov). 3. Nachal'nik prigotovitel'nogo tsekha Istomkinskoy pryadil'no-tkatskoy fabriki (for Figurina).

(Textile machinery)

(Yarn)

KOLPAKOV, A.M.; FIGURINA, Z.G.; YASHIN, V.I.

Effect of ballon dividers on the breakage of yarn during winding. Tekst. prom. 22 no.7:40-42 J1 162.

(MIRA 17:1)

1. Nachal'nik tkatskogo proizvodstva Istomkinskoy pryadil'notkatskoy fabriki (for Kolpakov). 2. Nachal'nik prigotovitel'nogo otdela Istomkinskoy pryadil'no-tkatskoy fabriki (for Figurina). 3. Starshiy instruktor Istomkinskoy pryadil'notkatskoy fabriki (for Yashin).

L 00761-67 ENP(j)/ENT(m)/T SOURCE CODE: UR/0113/66/000/004/0017/0019 AP6022850 ACC NR: AUTHOR: Kolpakov, A. P.; Yermilov, S. S. (Candidate of technical sciences) ORG: None TITLE: Camber of the rubber tires on a steerable semitrailer COURCE: Avtomobil'naya promyshlennost', no. 4, 1966, 17-19 TOPIC TAGS: tire, industrial truck, vehicle engineering ABSTRACT: The authors consider the effect of tire camber on the turning kinematics of an articulated truck with a steerable double-axle semitrailer. The trailer weight is conditionally assumed to be concentrated at two points: on the fifth wheel and at the center of the trailer frame. A formula is given for the centrifugal force of inertia away from the center of turning due to the weight of the trailer. This force is balenced by the total lateral force represented by the total geometric sum of the forces resulting from contact of the tires with the supporting surface. These forces depend on the camber of each wheel and are defined as the product of the coefficient of resistance to camber by the angle of camber for each wheel. Theoretical formulas are derived for calculating the camber and radius of turn for the center of the trailer frame as functions of the rate of motion for a steerable semitrailer. It is found that the turning radius increases considerably with speed. Experimental data show that camber

2 rientes 0 to	ormulas.	the steering link railers is 1-1.50 The angular gear is 1.1-1.15 to compe	age for controllable greater on the average atio of the drive for ensate for camber. O	r the
13/ SUBM DATE	none/ ORIG RE	F: 006		
<u>.</u>				
	• .			

KOLPAKOV, A. P.

Kolpakov, A. P. "On the problem of time limits for raising livestock among the Tadzhiks of Kulyab Oblast", Soobshch. Tadzh. filiala Akad. nauk SSSR, Issue 9, 1948, p. 30-32.

SO: U-3042, 11 March 53, (Letopia'nykh Statey, No. 10, 1949).

- 1, Kolpakov, A.P.
- 2. USSR (600)
- 4. History Kabodian
- 7. A page from the history of Kabodian. Soob. TFAN SSSR/no. 3, 1951.

9. Monthly list of Russian accessions. Library of Congress, March 1953, Unclassified.

- 1. ZHILIN, B. G., KOLPAKOV, A. P.
- 2. USSR (600)
- 4. Lumbering
- 7. Unloading full-length logs trucked to the river for free floating. Les prom No. 2

9. Monthly List of Russian Accessions, Library of Congress, April 1953, Uncl.

